de-humidifier





ND 328



20 Ltrs / Day extraction capacity



Recommended Upto 2500-3000 cu.ft indicative coverage area



Premium Brand From Singapore since 2003 in india



Digital Display to view / set humidity & temperature



Semi Permanent Built In Ionizer for fresh indoor air quality



Auto Restart resumes operation once power comes on



Auto Resume pre-set humidity levels maintained on power resumption







	U
	Š
	C
	_
	-
	-
	-
	π
	٠,
	Ċ
	_
- 1	_
	-
	_
	-
	(
	_
	а
	u
	=
	(
	_
- (<i>r r</i>
•	◡.

Extraction (30°C, 80% RH)	<i>l</i> /day	20
Recommended Coverage (Indicative) (Home)	cu.ft.	3500
Recommended Coverage (Indicative) (Industry)	cu.ft.	2500
Power consumption, Power supply 220V-240V/50Hz	watt	304
Negative Ion Density*		Up to 20 Million/cm ³
Air Flow	m³/ hr	225
Noise Level (Approx.)		Silent
Dimensions (W X D X H)	inches	14" x 10" x 24"
Tank Capacity	l	4
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R-134a
Empty Weight	kg	13.2
Running Temperature		5°C – 35°C
Programmable Timer		Yes



* Negative Ion Density* + Negative ion density measurement is based from source emission. ≥ 20 Million/cm3



















Food





Home

Healthcare

Pharma

R & D

Hotel Warehousing

Museum & Art Galleries