

OS165 Powerful Dehumidifier




165 ltrs/day
extraction capacity



Recommended up to 16500 cu.ft.
indicative coverage area



Stainless Steel Body
SS304 body – anti corrosive and easy cleaning



Corrosive Resistant Condenser Evaporator
long life and higher efficiency



Dual Drainage Option
water pump + water tank



Optimum Dehumidifying Performance
high air flow at 1800 m³/hr



Easy Mobility
with castors



OS165 dehumidifier

Specifications

Body Material	SS 304
Extraction (l/24hr) (30°C, 80% RH)	165 litres/day
Coverage Area	16500 cu. ft.
Dimensions	625*435*1600 mm
Power consumption, Power supply 220V-240V/50Hz	2120 watts
Electric Current(A)	9.6A
Air Flow	1800 m ³ /hr
Refrigerant	R-410a
Compressor	Panasonic (Rotary Type)
Noise Level (approx.)	≤ 63 db (A)
High Pressure	26 kgf/m ²
Low Pressure	8 kgf/m ²
Tank Capacity (SS tank)	6.5 litres
Water Pump	Max : 4 - 4.5 meters height
Weight	110 kg
Running Temperature	5°C – 35°C



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense