

AD 560 Robust De-humidification



60 Ltrs / Day extraction capacity recommended upto 6500 cu.ft



Made in Germany since 1990



Blue Dry Technology most energy efficient dehumidification @ 810 watts



Easy-To-Use Electronic eDRY displays RH level, kWh and operating hours



Optimum Dehumidifying Performance high air flow at 700 m³/hr



Dependable & Durable modular metal body



AD 560





Extraction (30°C, 80% RH)	<i>l</i> /day	60
De-humidifying performance / power consumption at **		
30°C / 80% RH	<i>l</i> /day	60 / 810 watts
27°C / 60% RH	<i>l</i> /day	37 / 700 watts
20°C / 60% RH	<i>l</i> /day	26 / 550 watts
Recommended Coverage (Indicative)*	cu.ft.	6500
Max. power consumption, Power supply 230V/50 Hz	watts	810
Air circulation rate	m³/h	Speed 1/2 = 425/700
Noise level (Approx.)	db	53
Dimensions (W X D X H)	inches	16" x 18" x 29"
Tank capacity		14l or condensate drainage
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R407c
Weight	kgs	36
Working temperature range		5°C – 34°C















Hotel











Museum & Art Galleries

Pharma

R & D

Warehousing

& Defense