

## AD 580 Robust De-humidification



78 Ltrs / Day extraction capacity recommended upto 8500 cu.ft



Made in Germany since 1990



Blue Dry Technology most energy efficient dehumidification @ 1400 watts



Easy-To-Use Electronic eDRY displays RH level, kWh and operating hours



Optimum Dehumidifying Performance high air flow at 820 m³/hr



Dependable & Durable modular metal body







Extraction (30°C, 80% RH)	<i>l</i> /day	78
De-humidifying performance / power consumption at **		
30°C / 80% RH	<i>l</i> /day	78 / 1070 watts
27°C / 60% RH	<i>l</i> /day	56 / 910 watts
20°C / 60% RH	<i>l</i> /day	40 / 740 watts
Recommended Coverage (Indicative)*	cu.ft.	8500
Max. power consumption, Power supply 230V/50 Hz	watts	1070
Air circulation rate	m³/h	Speed 1/2 = 600/886
Noise level (Approx.)	db	65
Dimensions (W X D X H)	inches	18" x 18" x 32"
Tank capacity		14l or condensate drainage
Humidity Setting		Electronic
Compressor		Rotary
Refrigerant		R410a
Weight	kgs	40
Working temperature range		5°C – 34°C

























Defense

Pharma

R & D

Hotel Warehousing