



AD 750 Heavy Duty Mobile De-humidifier



55 Ltrs / Day extraction capacity Recommended Upto 6000 cu.ft



Made in Germany since 1990



Blue Dry Technology most energy efficient dehumidification @ 900 watts



Easy-To-Use Electronic eDRY displays RH level, kWh and operating hours



Optimum Dehumidifying Performance high air flow at 710 m³/ hr



New Casing Technology with recyclable PE, UV stabilized



AD 750



Extraction (30°C, 80% RH)	<i>l</i> /day	55
De-humidifying performance / power consumption at **		
30°C / 80% RH	<i>l</i> /day	55 / 900 watts
27°C / 60% RH	<i>l</i> /day	34.1 / 780 watts
20°C / 60% RH	<i>l</i> /day	24.5 / 660 watts
Recommended Coverage (Indicative)*	cu.ft.	6000
Max. power consumption, Power supply 230V/50 Hz	watts	900
Air circulation rate	m³/h	710
Noise level (Approx.)	db	53
Dimensions (W X D X H)	inches	21" x 20" x 35"
Tank capacity		121 or condensate drainage
Humidity Setting		Mechanical
Compressor		Rotary
Refrigerant		R407c
Weight	kgs	42
Working temperature range		5°C – 32°C





Specifications





Pharma













R & D

2

Printing Warehousing

Food

Defense Art Galleries

Museum &