

OS110 Robust Dehumidifier



110 ltrs/day
extraction capacity



Recommended up to 10500 cu.ft.
indicative coverage area



Stainless Steel Body
SS304 body – anti corrosive and easy cleaning



Corrosive Resistant Condenser Evaporator
long life and higher efficiency



Dual Drainage Option
water pump + water tank



Optimum Dehumidifying Performance
high air flow at 900 m³/hr



Easy Mobility
with castors



OS110 dehumidifier

Specifications

Body Material	SS 304
Extraction (l/24hr) (30°C, 80% RH)	110 litres/day
Coverage Area	10500 cu. ft.
Dimensions	495*420*1050 mm
Power consumption, Power supply 220V-240V/50Hz	1660 watts
Electric Current(A)	6.3A
Air Flow	900 m³/hr
Refrigerant	R-410a
Compressor	Panasonic (Rotary Type)
Noise Level (approx.)	≤ 58 db (A)
High Pressure	26 kgf/m2
Low Pressure	8 kgf/m2
Tank Capacity (SS tank)	6.5 litres
Water Pump	Max : 4 - 4.5 meters height
Weight	60 kg
Running Temperature	5°C – 35°C



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense